



TLI-DN217

DOWNLIGHT

TECHNICAL

Materials of Optics	PC
Materials of Housing	Aluminum
Light Source	CREE/Bridgelux
Color Temperature	3000/4000/5000K
Luminous Efficiency@4000K	90lm/W
CRI	≥90
Beam Angle(°)	15°/24°/38°
UGR	<19(24°)
Lifetime(hr)	50,000H
Product Finishing	White / Black

FEATURES & BENEFITS

CCT Selection	3CCT
LED Driver	Built-out
Dimming Option	Triac/0-10v/DALI
Ingress Protection (IP Rating)	IP20
Power Factor(PF)	≥ 0.9
Certification	SAA/ RoHS/CE

DATA SHEET

CODE	WATT	INPUT VOLTAGE	DIMENSION(mm)	CUT-OUT(mm)	LUMEN(±5%)
TLI-DN217-3W	3W	AC200-240V	Ø35x45mm	Ø30mm	210lm
TLI-DN217-5W	5W	AC200-240V	Ø60x81mm	Ø55mm	415lm
TLI-DN217-7W	7W	AC200-240V	Ø60x81mm	Ø55mm	620lm
TLI-DN217-10W	10W	AC200-240V	Ø75x100mm	Ø65-70mm	895lm
TLI-DN217-12W	12W	AC200-240V	Ø75x100mm	Ø65-70mm	1055lm

EXPERIENCE

